Safety Data Sheet

Approved by ECOCERT RAW MATERIAL

ZLEY®BIOCARE-CHA

Caprylhydroxamic acid

ZLEY

Version No:**2.0** Safety Data Sheet according to GB/T16483,GB/T17519 Standard requirements Project number: RF-SDS400802 Issue Date:07/23/2022

Part 1: Chemicals and Corporate Identity

Product name

	Name of the chemical	Caprylhydroxamic acid
	Alias	None
.1	Molecular formula	C ₈ H ₁₇ NO ₂
4	Other identification methods	None
	CAS No.	7377-03-9

Manufacturer importer or supplier

Corporate name	Zley Holdings (Suzhou) Co., Ltd.
Corporate address	10th Floor, Building 2, Yushan Square, High-tech Zone, Suzhou City, Jiangsu Province Zip code: 215000
Tel:	0512-87775990/18626205929
Fax:	0512-87775990
Website	http://www.zleyholdings.com
E-mail	info@zleyholdings.com

Emergency telephone

Emergency telephone	+86 4000928866
---------------------	----------------

Part 2: Hazard Overview

ISO C

ZLE

Classification of substances and mixtures Emergency overview Solid· Non-combustible Irritant to eyes May cause respiratory irritation Irritant to skin

	Skin corrosion/irritation category 2, severe eye
Hazard category	damage/eye irritation category 2A, specific
	target organ toxicity one time exposure
	category3

Approved by ECOCERT RAW MATERIAL

REACH

Label Elements

4	L'Y	The state	GHS pictogram	84 1.48		LLET L
			Signal word	Warning	1	4

Hazard statement

H315	Cause skin irritation		
H319	Cause severe eye irritation	A A	A
H335	May cause respiratory irritation	Y	

Nary statement: preventive measures

P101	In case of medical treatment: please take with product container or label	175	125	1
P102	Keep of reach of children		.1	
P103	Please the label before use	A.	4.	
P271	Can only be used outdoors or in a well-ventilated area	The	1×	T

Precautionary statement: incident response

P305+P351+P338	In case of entering into the eyes: rinse cautiously with water for several minutes. If contact lenses are worn and can be removed easily, removed
	the contact lenses, and continue to rinse.
P312 In case you feel sick, call the detoxication center or call a d	
P337+P313 In case eye irritation persists: see a doctor/medical treatment	
P307+p352	In case the skin is contaminated: wash with plenty of soap and water

Precautionary statement: safe storage

ISO SGS (REACH

P405	The depository must be locked.	1 V	19	1.2
P403+P233	Store in a well-ventilated place,			
	and keep the container closed.			

Approved by ECCOCERT RAW MATERIAL

Precautionary statement: disposal consideration

P501	The dispose of contents/container should be conducted in accordance with
	local regulations.

Physical and chemical hazards Solid Non-combustible

Health hazard

集團

Inhalation	The substance can cause respiratory tract irritation to some people, and the human body's response to the irritation will cause further lung injury. In case people with respiratory dysfunction, respiratory diseases such as emphysema or chronic tracheitis inhale high concentrations of particles, further loss of function may be caused. In case of previous circulatory or nervous system damage, or in case renal injury has been persistently existed, and excessive exposure is caused by treatment or use of the substance, those who may be exposed to greater risks should be screened appropriately.
Ingestion	The substance is not classified as "harmful if swallowed" according to EU directives or other classification systems, which is due to the lack of conclusive animal or human evidence. The ingestion of the substance can still cause harm to the health of individuals, especially to those with previous obvious organic damage (such as liver and kidney). Currently, harmful or toxic substances are generally defined on the basis of the dose that causes death but not on the basis of the dose that causes illness (disease and discomfort). Gastrointestinal tract discomfort may cause nausea and vomiting. However, the ingestion of trace of the substance in the workplace is not considered dangerous.
Skin contact	Some people's skin contact with this substance can lead to inflammation. The substance can exacerbate the original dermatitis disease. Skin contact is not considered to be able to cause effects harmful to health (classified in accordance with EU directive), but the substance may still cause health damage in case of entering the body through wounds, lesions or abrasions. Unhealed wounds, abraded or irritated skin should not be exposed to the substance. The entry into the body through wounds, lesions or abrasions may cause harmful effects of systemic injury. The skin should be examined before using the substance, and the substance can only be used after ensuring that any injury is properly protected.

Eyes	The substance can irritate and damage the eyes of some people.	
Chronic	Long term exposure to respiratory irritants may lead to tracheal diseases, including expiratory dyspnea and related systemic diseases. Limited evidence suggests that repeated or long-term occupational exposure may contribute to cumulative health effects in relation to organs or biochemical systems.	

Approved by ECOCERT RAW MATERIAL

Environmental hazards: Please refer to Part 12

Other hazardous nature

Part 3: Component / Composition Information

Material

ZLEY

妝萊集

CAS number	Concentration or concentration range(mass fraction%)	Component	
7377-03-9	100	Caprylhydroxamic acid	

Part 4: First Aid Measures

First aid

Eye contact	In case the eyes contact with this product: Rinse immediately with running water. Ensure that the eyes are thoroughly cleaned by lifting the upper and lower eyelids from time to time.In case the pain persists or relapses, seek medical advice immediately.
	Contact lenses should only be removed by trained personnel after eye injury In case of skin contact:
Skin contact	Immediately remove all contaminated clothing, including shoes and socks; Rinse skin and hair with running water (use soap if possible); In case of irritation, seek medical advice.
A A	If smoke or combustion products are inhaled, remove the patient from the contaminated area. Keep the patient lying flat. Pay attention to keep warm and rest. Remove prostheses such as dentures before starting first aid as far as possible to prevent
Inhalation	from blocking the respiratory tract. In case of respiratory arrest, artificial respiration should be carried out. It is better to use the artificial respirator with stop valve or bag valve mask or pocket mask, and cardiopulmonary resuscitation should be performed if necessary. Take the patient to hospital or seek medical service immediately.
Ingestion	Provide a glass of water immediately. First aid is usually not required. If there is any doubt, contact the Poisons Information Centre or contact a doctor.

Advice on protecting rescuers Special tips for doctors Symptomatic treatment

REACH

Part 5: Fire Protection Measures

ISO C

Fire extinguishing agent

There are no restrictions on the type of fire extinguishing agent. Use fire extinguishing media suitable for the surrounding environment

Special Hazard

E.

Fire taboo	No information available.

Matters needing attention and protective measures for fire extinction

	Notify the fire brigade, and inform it of the location and hazard characteristics of
	the accident.
	Wear respiratory equipment and protective gloves only in case of fire.
Fire-fighting measures	Take all possible measures to prevent spillage from entering sewers or water
1	courses.
	Use fire-fighting procedures suitable for the surrounding environment.
	Non-combustible
Fire/Explosion hazards	There is no major fire risk, however, the container may burn.
4	May release toxic fumes

Part 6: Accidental Release Measures

Protective measures for operators, protective equipment and emergency disposal procedures

Please refer to Part 8.

Preventive measures to prevent from secondary disasters Please refer to the above parts.

Environmental protection measures: Please refer to Part 12.

Internment, removal methods and used disposal materials of leaked

A small amount of leakage	Clean up all leakages immediately. Avoid inhalation of dust and avoid contact with skin and eyes. Wear protective clothing, gloves, safety goggles and dust masks, Use dry cleaning procedures to avoid the generation of dust.
A large amount of leakage	Moderate level hazard. Warning: notify all personnel in the area. Report to the emergency departments and inform them of the accident location and hazard characteristics.Wear protective clothes

Approved by ECOCERT RAW MATERIN

REACH

The recommendations for personal protective equipment are shown in Part 8 of the SDS

Part 7: Operation Disposal and Storage

ISO C

ΣE.

Matters needing attention for operation disposal

Safe operation	Prevent all contact, including inhalation.
	Wear protective clothing in case of exposure to the hazard.
	Use in a well-ventilated area. Prevent the product from gathering in
	low-lying areas.
	Store in the original container.Keep the container safe and sealed.Store in a
Other information	cool,dry and well ventilated place.
4	Store in a lace away from incompatible materials and food containers.

Matters needing attention for storage

Proper container		Polyethylene or polypropylene containers. Check all containers to ensure that the labels are clear and there is no leakage.				
Storage prohibition	No data available.	A		-	- P	

Part 8: Contact Control and Individual Protection

Control parameters, Occupational contact limits and Compositional data: None

Emergency restrictions

Ingredient	Name of the substance	TEEL-1	TEEL-1	TEEL-1
Caprylhydroxamic acid	None	None	None	None



→ 	Use engineering control to eliminate hazards, or set up a barrier between workers and
	hazards. Well-designed engineering
	control can effectively protect workers, and usually can improve the protection level
	without being affected by the interaction between workers.
	The basic types of engineering control include:
	Reduce risks through process control changing operation activities or process flow
Engineering	mode.
control	Close and/or isolate emission source, so as to physically isolate the target hazard and
	workers, as well as the ventilation system able to add a "add fresh air" and "get rid of
	dirty air" strategically in the workplace. In case the design is reasonable, the ventilation
	system can eliminate or reduce air pollution. The design of the ventilation system
	must be in accordance with the specific process and the chemicals or contaminants
	used.
	Employers may need to use multiple types of control measures to
	prevent employees from overexposure.
Personal	
protective	
equipment	
1 1	
	Safety glasses with side frame protection. Chemical goggle.
Eye and	Contact lenses may cause special hazards; soft contact lenses may absorb and enrich
	irritants. Each workplace or work platform should formulate a written policy document
face protection	irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions
face protection	irritants. Each workplace or work platform should formulate a written policy document
face protection	irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below
face protection	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US
face protection	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards).
face protection	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with
face protection	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes
face protection	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with
face protection	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is
face protection	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is
face protection Skin protection Hand/foot	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is expected to contact for only a short time, it is recommended to use gloves with IP grade of 3 or higher (penetration time should be greater than 60 minutes according to EN
face protection Skin protection Hand/foot	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is expected to contact for only a short time, it is recommended to use gloves with IP grade of 3 or higher (penetration time should be greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards).
face protection Skin protection Hand/foot	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is expected to contact for only a short time, it is recommended to use gloves with IP grade of 3 or higher (penetration time should be greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). The contaminated gloves should be replaced.
face protection Skin protection Hand/foot	 irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is expected to contact for only a short time, it is recommended to use gloves with IP grade of 3 or higher (penetration time should be greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). The contaminated gloves should be replaced. Experience has shown that the following polymers as glove materials are suitable for th
face protection Skin protection Hand/foot	irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is expected to contact for only a short time, it is recommended to use gloves with IP grade of 3 or higher (penetration time should be greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). The contaminated gloves should be replaced. Experience has shown that the following polymers as glove materials are suitable for th protection of undissolved, dry and abrasive free solids.
face protection Skin protection Hand/foot	irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is expected to contact for only a short time, it is recommended to use gloves with IP grade of 3 or higher (penetration time should be greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). The contaminated gloves should be replaced. Experience has shown that the following polymers as glove materials are suitable for th protection of undissolved, dry and abrasive free solids. Chloroprene rubber Nitrile rubber Butyl rubber Fluororubber Polyvinyl chloride
face protection Skin protection Hand/foot	irritants. Each workplace or work platform should formulate a written policy document on contact lens wear or use restrictions Please refer to hand protection: below Choose gloves tested according to relevant standards (such as European EN 374, US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is expected to contact for only a short time, it is recommended to use gloves with IP grade of 3 or higher (penetration time should be greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). The contaminated gloves should be replaced. Experience has shown that the following polymers as glove materials are suitable for th protection of undissolved, dry and abrasive free solids.

Approved by ECOCERT RAW MATERIAL

	Y [®]			REACH	Approved by ECOCERT RAW MATERIAL
--	----------------	--	--	-------	--

Body	Please refer to other protection: below	- 40 [×]		
protection		A Y		
Other	Working clothes			
	PVC (polyvinyl chloride) apron Protective cream			
protection	Skin cleaning cream			
Thermal	None	4		
hazard			.1	

Respiratory system protection

(AS/NZS year 1716 and 1715, ANSI Z88 EN 143:000 and 149:001, or equivalent to the state),

Respirators may be necessary to be used when engineering and management controls cannot effectively prevent exposure.

The use of respiratory protection should depend on professional advice and judgment, including the consideration of toxicological information, exposure measured data, frequency, and the possibility of worker exposure, so as to ensure that users are not subjected to high heat loads that may lead to heat stress or thermal fatigue as a result of personal protective equipment (a full filter with power assist and positive pressure can be selected).

Published occupational contact (exposure) limits, which may be mandatory by the government or recommended by the seller, will help to determine whether the selected respiratory protective equipment is effective enough.

When the part properly selected and tested as part of a complete respiratory protection measure system, certified respirators can effectively protect workers from inhalation of particulate matter.

When there is a considerable amount of dust in the air, use an approved positive pressure breathing mask.

Try to avoid conditions producing dust.

Part 9: Physicochemical Properties

Approved by ECOCERT RAW MATERIAL

Appearance		White crystalline powder	
Physical state	Powder solid	Relative density (water=1)	None
Odor	Odourless	Partition coefficient n-octyl alcohol/ water	None
Odor threshold	None	Autoignition temperature (vermin)	None
pH (by supply)	None	Decomposition temperature	None
Melting point/ freezing point (°C)	78-82	Viscosity (cSt)	Not applicable
Initial boiling, point and point range (℃)	None	Molecular weight (g/mol)	159.23
Flash point (°C)	None	Taste	None
Evaporation rate	None	Explosive property	None
Inflammability	Non-flammable	Oxidation property	None
Upper explosive limit (%)	None	Surface tension (dyn/cm ormN/m)	None
Lower explosive limit (%)	None	Volatility composition (%volume)	None
Vapor pressure (kPa)	None	Gas group	None
Vapor density (air = 1)	Not applicable	The pH value of the solution (1%)	None
Solubility in water (g / L)	None	VOC g/L	None

Basic physicochemical properties

Part 10: Stability and Reactivity

ISO (C) (REACH

ZLEY

Reactivity	Please refer to part 7		
Stability	Existence of incompatible substances. The substance is considered to be stable. Polymerization without the occurrence of hazards.		
Hazardous reaction	Please refer to part 7		
Conditions that should be avoided	Please refer to part 7		
Conditions that should be avoided	Please refer to part 7		
Hazardous decomposition products	Please refer to part 5		

Approved by ECOCERT RAW MATERIA

Part 11: Toxicological Information

Caprylhydroxamic acid	Toxicity		
	Oral (Rat)		
	LD50: > 2600 mg / kg	.1	4

Part 12: Ecological Information

Ecotoxicity

Components	Destination	Test duration (hours)	Туре	Value	Source
Caprylhydroxamic acid	N/A	-N/A	N/A	N/A	N/A
Caprylhydroxamic acid	N/A	N/A	N/A	N/A	N/A

It is prohibited to be discharged into sewers or water bodies.

Persistence and degradability

Component	Persistence: water/soil	Persistence: air	
Caprylhydroxamic acid	Low	Low Low	

Potential bioaccumulation

Component	Bioaccumulation	
Caprylhydroxamic acid	Low	

Mobility in soil **Other adverse effects:** No data available

Approved by ECOCERT

Part 13: Disposal Considerations

Disposal considerations

, E

Waste chemicals	Recycle as far as possible, or consult manufacturer about the relevant recyclable methods.Consult local waste management department about relevant disposal considerations methods.Bury the residues in the approved landfill. If possible, recycle the containers, or dispose wastes in the approved landfill.
Contaminated Packaging	Please refer to the above parts.
Transportation precautions	Please refer to the above parts.

Part 14: Transport Information

Packaging mark

Marine pollutants	None
-------------------	------

Land transport (UN): not regulated as dangerous goods for transportation. Air transport (ICAO-IATA /DG, 61th edition): not regulated as dangerous goods for transportation.

Maritime transport (IMDG-Code / GGVSee, 39-18): not regulated as dangerous goods for transportation.

Conduct bulk transportation according to Appendix 1 and IBC code of MARPOL: N/A

Precautions for transportation: None **Packing method:** Please refer to Part 7

Part 15: Regulatory Information

ISO C

OSHA: Process Safety Management: Material is not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemical.

Survey, nomini min provinci no grandi specific for the product in discussion			
INCI	NCI Chemical names		EC No.
Caprylhydroxamic acid N-hydroxyoctanamide		7377-03-9	230-936-7
European Inventory of Existing Commercial Substances (EINECS)			Listed
United States Toxic Substances Control Act (TSCA) Inventory			Listed
Inventory of Existing Chemical Substances in China (China IECSC)			Not Listed

Safety, health and environmental regulations specific for the product in question

ECOCERT

REACH

Part 16: Other Information

Other information

(material) safety data sheet (SDS) is used as the communication tool of hazardous information, which should be used to assist in risk assessment. Many factors can be used to determine whether a hazard in the workplace or in other locations should be reported as dangerous. Risk can be determined by reference to exposure. The scale of use, frequency of use and existing.

Abbreviations and acronyms

PC-TWA: Permissible Concentration-Time Weighted Average refers to the average permissible exposure concentration of 8-hour working days and 40-hour working weeks regulated with the time as the weight.

PC-STEL: Permissible Concentration Short Term Exposure Limit refers to the concentration allowed to be exposed for a short time (15 min) under the premise of complying with PC-TWA

IARC: International Agency for Research on Cancer.

ACGIH: American Conference of Government Industrial Hygienists

STEL:Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit

IDLH:Immediately Dangerous to Life or Heath Concentrations

OSF:Odor Safety Factor

NOAEL:No Observed Adverse Effect Level

LOAEL:Lowest Observed Adverse Effect Level

TLV:Threshold Limit Value

LOD:Limit of Detection

OTV:Odour Threshold Value