









Safety Data Sheet

ZLEY®Elmtrifun

Butylene Glycol, Ulmus Davidiana Root Extract, Water

Project number:

Version No:1.0

Issue Date: 07/15/2022

Safety Data Sheet according to GB/T164483,GB/T17519

Standard requirements

Part 1: Chemicals and corporate identity

Product name

Г	4	Name of the chemical	Butylene	Glycol,	Ulmus	Davidiana	Root
y	♦		Extract, V	Vater			
		Alias	None	7			
		Other identification methods	None	1		1	1
	4	CAS No.	107-88-0,	7732-1	18-5		

Manufacturer, importer or supplier

Corporate name	Zley Holdings (Suzhou) Co., Ltd.
	10th Floor, Building 2, Yushan Square,
Corporate address	High-tech Zone, Suzhou City, Jiangsu Province
	Zip code: 215000
Tel:	+86 512-87775990/18626205929
Fax:	0512-87775990
Website	http://www.zley.net/
E-mail	Info@holdings.com

Emergency telephone

Emergency telephone	+86 4000928866











Part 2: Hazard overview

Classification of substances and mixtures Emergency overview.

Solid Non-combustible.

Irritant to eyes.

May cause respiratory irritation. Irritant to skin

	Skin corrosion/irritation category 2, severe
Hazard category	eye damage/eye irritation category 2A,
	specific target organ toxicity one time
	exposure category 3

Label Elements

177	177	GHS pictogram	
1.5	45	Signal word	Warning

Hazard statement

H315	Cause skin irritation
H319	Cause severe eye irritation
H335	May cause respiratory irritation

Precautionary statement: preventive measures

P101	In case of medical treatment: please take with product container or label		
P102	Keep out of reach of children		
P103	Please read the label before use		
P271	Can only be used outdoors or in a well-ventilated area		

Precautionary statement: incident response

	In case of entering into the eyes: rinse cautiously
P305+P351+P338	with water for several minutes. If contact lenses
	are worn and can be removed easily, remove the
19 18 18 18 18	contact lenses, and continue to rinse.
	In case you feel sick, call the detoxication
P312	center or call a doctor.
P337+P313	In case eye irritation persists: see a
13 17 17 T	doctor/medical treatment
P307+p352	In case the skin is contaminated: wash with
	plenty of soap and water
	· · · · · · · · · · · · · · · · · · ·











Precautionary statement: safe storage

P405	The depository must be locked.
P403+P233	Store in a well-ventilated place, and keep the
	container closed.

Precautionary statement: disposal consideration

	12 12 17 1	The dispose	of	contents/conta	iner sho	ould be
	P501	conducted	in	accordance	with	local
4		regulations.				*

Physical and chemical hazards Solid Non-combustible

Health hazard

Inhalation	The substance can cause respiratory tract irritation to some people, and the human body's response to the irritation will cause further lung injury. In case people with respiratory dysfunction, respiratory diseases such as emphysema or chronic tracheitis inhale high concentrations of particles, further loss of function may be caused. In case of previous circulatory or nervous system damage, or in case renal injury has been persistently existed, and excessive exposure is caused by treatment or use of the substance, those who may be exposed to greater risks should be screened appropriately.
Ingestion	The substance is not classified as "harmful if swallowed" according to EU directives or other classification systems, which is due to the lack of conclusive animal or human evidence. The ingestion of the substance can still cause harm to the health of individuals, especially to those with previous obvious organic damage (such as liver and kidney). Currently, harmful or toxic substances are generally defined on the basis of the dose that causes death but not on the basis of the dose that causes illness (disease and discomfort). Gastrointestinal tract discomfort may cause nausea and vomiting. However, the ingestion of trace of the substance in the workplace is not considered dangerous.
Skin contact	Some people's skin contact with this substance can lead to inflammation. The substance can exacerbate the original dermatitis disease. Skin contact is not considered to be able to cause effects harmful to health (classified in accordance with EU directive), but the substance may still cause health damage in case of entering the body through wounds, lesions or abrasions. Unhealed wounds, abraded or irritated skin should not be exposed to the substance. The entry into the body through wounds, lesions or abrasions may cause harmful effects of systemic injury. The skin should be examined before using the substance, and the substance can only be used after ensuring that any injury is properly protected.









1	Eyes	The substance can irritate and damage the eyes of some people.			
7		Long term exposure to respiratory irritants may lead to tracheal diseases,			
	including expiratory dyspnea and related systemic diseases.				
	Chronic Limited evidence suggests that repeated or long-term occupational exp				
1	may contribute to cumulative health effects in relation to organs or biochemics				
,		systems.			

Environmental hazards: please refer to Part 12.

Other hazardous nature.

Part 3: Component / composition information

Material

CAS number	Concentration or concentration range (mass fraction%)	Component
107-88-0	65	Butylene Glycol
	25	Ulmus Davidiana Root
	25	Extract
7732-18-5	10	Water

Part 4: First aid measures

First aid

Eye contact	In case the eyes contact with this product: Rinse immediately with running water. Ensure that the eyes are thoroughly cleaned by lifting the upper and lower eyelids from time to time. In case the pain persists or relapses, see medical advice immediately, Contact lenses should only be removed by trained
4 4	personnel after eye injury
177	In case of skin contact: Immediately remove all contaminated clothing, including shoes and socks; Rinse skin and hair with
Skin contact	running water (use soap if possible);
	In case of irritation, seek medical advice.











	If smoke or combustion products are inhaled, remove the patient
	from the contaminated area.
	Keep the patient lying flat. Pay attention to keep warm and rest.
	Remove prostheses such as dentures before starting first aid as far
	as possible to prevent from blocking the respiratory tract.
	In case of respirator arrest, artificial respiration should be carried
	out. It is better to use the artificial respirator with stop valve or
Inhalation	bag valve mask or pocket mask, and cardiopulmonary
	resuscitation should be performed if necessary.
$\Phi_{\mathbf{A}}^{\mathbf{Y}}$	Take the patient to hospital or seek medical service immediately.
1 1	Provide a glass of water immediately.
Ingestion	First aid is usually not required. If there is any doubt, contact the
	Poisons Information Centre or contact a doctor.

Advice on protecting rescuers Special tips for doctors Symptomatic treatment.

Part 5: Fire protection measures

Fire extinguishing agent

There are no restrictions on the type of fire extinguishing agent. Use fire extinguishing media suitable for the surrounding environment.

Special hazard

4 = 4 4 1	
Fire taboo	No data available.

Matters needing attention and protective measures for fire extinction

19 19 11 11 11 11 11 11 11 11 11 11 11 1	Notify the fire brigade, and inform it of the location and hazard characteristics of the accident. Wear respiratory
V V	equipment and protective gloves only in case of fire.
Fire-fighting measures	Take all possible measures to prevent spillage from entering
♠ ♦	sewers or water courses.
12 12 1	Use fire-fighting procedures suitable for the surrounding
	environment.
A .A .	Non-combustible
Fire/Explosion hazards	There is no major fire risk, however, the container may burn.
1, 1, 1, 1,	May release toxic fumes

Part 6: Accidental release measures

Protective measures for operators, protective equipment and emergency disposal procedures: Please refer to Part 8.











Preventive measures to prevent from secondary disasters: Please refer to the above parts.

Environmental protection measures: Please refer to Part 12.

Internment, removal methods and used disposal materials of leaked chemicals

4 4	Clean up all leakages immediately.
A small amount of	Avoid inhalation of dust and avoid contact with skin and eyes.
leakage	Wear protective clothing, gloves, safety goggles and dust masks,
	Use dry cleaning procedures to avoid the generation of dust.
4	Moderate level hazard.
A large amount of	Warning: notify all personnel in the area.
leakage	Report to the emergency departments and inform them of the accident
1 4	location and hazard characteristics. Wear protective clothes.

The recommendations for personal protective equipment are shown in Part 8 of the SDS.

Part 7: Operation disposal and storage

Matters needing attention for operation disposal

Safe operation	Prevent all contact, including inhalation. Wear protective clothing in case of exposure to the hazard. Use in a well-ventilated area. Prevent the product from gathering in low-lying areas.
	Store in the original container. Keep the container safe and sealed. Store in a cool, dry and well ventilated place.
Other information	Store in a lace away from incompatible materials and food containers.

Matters needing attention for storage

V	TV V	Polyethylene or polypropylene containers.
1	Proper container	Check all containers to ensure that the labels are clear and
		there is no leakage.
4,7	Storage prohibition	No data available.

Part 8: Contact control and individual protection

Control parameters, Occupational contact limits and Compositional data: None.

Emergency restrictions











Ingredient	Name of the substance	TEEL-1	TEEL-1	TEEL-1
Butylene Glycol	None	None	None	None
Ulmus Davidiana Root Extract	None	None	None	None
Water	None	None	None	None

Contact control

Engineering control	Use engineering control to eliminate hazards, set up a barrier between workers and hazards. Well-designed engineering control can effectively protect workers, and usually can improve the protection level without being affected by the interaction between workers. The basic types of engineering control include: Reduce risks through process control changing operation activities or process flow mode. Close and/or isolate emission source, so as to physically isolate the target hazard and workers, as well as the ventilation system able to add a "add fresh air" and "get rid of dirty air" strategically in the workplace. In case the design is reasonable, the ventilation system can eliminate or reduce air pollution. The design of the ventilation system must be in accordance with the specific process and the chemicals or contaminants used. Employers may need to use multiple types of control measures to prevent employees from overexposure.
Personal protective equipment	
Eye and face protection	Safety glasses with side frame protection. Chemical goggle. Contact lenses may cause special hazards; soft contact lenses may absor and enrich irritants. Each workplace or work platform should formulate a writter policy document on contact lens wear or use restrictions
Skin protection	Please refer to hand protection: below.
Hand/foot protection	Choose gloves tested according to relevant standards (such as European EN 374 US F739, AS/NZS2161.1 or national equivalent standards). In case of long-term contact or repeated contact, it is recommended to use gloves with IP grade of 5 or higher (the penetration time should be greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). If it is expected to contact for only a short time, it is recommended to use gloves with IP grade of 3 or higher (penetration time should be greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent standards). The contaminated gloves should be replaced. Experience has shown that the following polymers as glove materials are suitable for the protection of undissolved, dry and abrasive free solids.
	Chloroprene rubber Nitrile rubber Butyl rubber Fluororubber Polyvinyl chloride Gloves should frequently be checked for wear and degradation.











_		
	Body	Please refer to other protection: below.
<	protection	
	1	Working clothes
	Other protection	PVC (polyvinyl chloride) apron Protective cream
		Skin cleaning cream
	Thermal	None
	hazard	

Respiratory system protection

(AS/NZS year 1716 and 1715, ANSI Z88 EN 143:000 and 149:001, or equivalent to the

Respirators may be necessary to be used when engineering and management controls cannot effectively prevent exposure.

The use of respiratory protection should depend on professional advice and judgment, including the consideration of toxicological information, exposure measured data, frequency, and the possibility of worker exposure, so as to ensure that users are not subjected to high heat loads that may lead to heat stress or thermal fatigue as a result of personal protective equipment (a full filter with power assist and positive pressure can be selected).

Published occupational contact (exposure) limits, which may be mandatory by the government or recommended by the seller, will help to determine whether the selected respiratory protective equipment is effective enough.

When the part properly selected and as part of a complete respiratory protection measure system, certified respirators can effectively protect workers from inhalation of particulate

When there is a considerable amount of dust in the air, use an approved positive pressure breathing mask.

Try to avoid conditions producing dust.











Part 9: Physicochemical properties

Basic physicochemical properties

Inspection Items	Technical Index
Appearance	Light yellow transparent liquid.
Oder	Characteristic
ULMUS DAVIDIANA ROOT EXTRACT	23%-28%
Pb	<10 (mg/kg)
Hg	<1 (mg/kg)
As	<2 (mg/kg)
Cd	<5 (mg/kg)
Aerobic bacterial count	<1000cfu/g
Yeast and Mold	<100cfu/g
Thermotoletant coliform	Not detectable/g
Staphylococcus aureus	Not detectable/g
Pseudomonas aeruginosa	Not detectable/g

Part 10: Stability and reactivity

Reactivity	Please refer to part 7
Stability	Existence of incompatible substances. The substance is considered to be stable.
A A A	Polymerization without the occurrence of hazards.
Hazardous reaction	Please refer to part 7
Conditions that should be avoided	Please refer to part 7
Prohibited substances	Please refer to part 7
Hazardous decomposition products	Please refer to part 5











Part 11: Toxicological information

177 17	Acute Toxicity	Irritation
Butylene Glycol	LD50 Oral rat(male): 22,800 mg / kg LD50 Dermal - Rabbit -> 20,000 mg/kg	Skin Irritation Rabbit Result:Mild skin irritation-4h Serious eye damage/eye irritation Rabbit Result: Irritation to eyes, reversing within 7 days - 18 h Respiratory or skin sensitization: No data available Germ cell mutagenicity No data available

Ulmus Davidiana	Acute Toxicity	Irritation
Root Extract	Not data available	Not data available

	1	Acute Toxicity	Irritation
	4	\$ \$ \phi \ \dagger \da	Skin Irritation No data available
Water	17	LD50 Oral rat - > 90,000 mg / kg	Serious eye damage/eye irritation No data available Respiratory or skin sensitization:
	17.6		No data available Germ cell mutagenicity No data available

Part 12: Ecological information

Ecotoxicity

Butylene Glycol

Butylette Gryce)1 ×				
Destination	Test duration (hours)	Туре	Value	Source	
LC50	96	Orange-red killifish	> 100 mg/l	OECD Test Guideline 203	
EC50	48	Water flea	> 1000 mg/l	OECD Test Guideline 202	
ErC50	72	Green algae	> 1070 mg/l	OECD Test Guideline 201	











Ulmus Davidiana Root Extract No data available

Water

No data available

It is prohibited to be discharged into sewers or water bodies.

Persistence and degradability

Component Biodegradability	
Butylene Glycol	aerobic - Exposure time 29 d Result: 81 % - Readily biodegradable. (OECD Test Guideline 301B)
Ulmus Davidiana Root Extract	No data available
Water	No data available

Potential bioaccumulation

Component Bioaccumulation	
Butylene Glycol	No data available
Ulmus Davidiana Root Extract	No data available
Water	No data available

Mobility in soil

Component	Mobility	
Butylene Glycol	No data available	
Ulmus Davidiana Root Extract	No data available	
Water	No data available	

Other adverse effects: No data available

Part 13: Disposal considerations

Disposal considerations

Waste chemicals:	Recycle as far as possible, or consult manufacturer about the	
Y 18 1	relevant recyclable methods.	
Consult local waste management department about relevant dispos		
considerations methods.		
	Bury the residues in the approved landfill.	
Y 1 Y	If possible, recycle the containers, or dispose wastes in the	
4 4	approved landfill.	











Contaminated packaging:	Please refer to the above parts.	Ī
Transportation precautions:	Please refer to the above parts.	

Part 14: Transport information

Packaging mark

Marine pollutants	None A

Land transport (UN): not regulated as dangerous goods for transportation.

Air transport (ICAO-IATA /DG, 61th edition): not regulated as dangerous goods for transportation.

Maritime transport (IMDG-Code / GGVSee, 39-18): not regulated as dangerous goods for transportation.

Conduct bulk transportation according to Appendix 1 and IBC code of MARPOL: N/A.

Precautions for transportation: None. Packing method: Please refer to Part 7.

Part 15: Regulatory information

OSHA: Process Safety Management: Material is not listed in appendix A of 29 CFR 1910.119 as highly hazardous chemical.

Safety, health and environmental regulations specific for the product in question

INCI	Chemical names	CAS No.	EC No.
Butylene Glycol	107-88-0	203-529-7	
European Inventory of Existing Commercial Substances (EINECS)			Listed
United States Toxic Substances Control Act (TSCA) Inventory			Listed
Inventory of Existing Chemical Substances in China (China IECSC)			Listed

INCI	Chemical names	CAS No.	EC No.
Ulmus Davidiana	Bakuchiol[(1E,3S)-3-ethenyl-3,7-dim		<i>y</i> 1
Root Extract	ethyl-1,6-octadien-1-yl]phenol		
European Inventory of Existing Commercial Substances (EINECS)			Not Listed
United States Toxic Substances Control Act (TSCA) Inventory			Not Listed
Inventory of Existing Chemical Substances in China (China IECSC)			Not Listed











INCI	Chemical names	CAS No.	EC No.
Water	Aqua	7732-18-5	231-791-2
European Inventory of Existing Commercial Substances (EINECS)			Listed
United States Toxic Substances Control Act (TSCA) Inventory			Listed
Inventory of Existing Chemical Substances in China (China IECSC)			Listed

Part 16: Other Information

Other information

(material) safety data sheet (SDS) is used as the communication tool of hazardous information, which should be used to assist in risk assessment. Many factors can be used to determine whether a hazard in the workplace or in other locations should be reported as dangerous. Risk can be determind by reference to exposure. The scale of use, frequency of use and existing.

Abbreviations and acronyms

PC-TWA: Permissible Concentration-Time Weighted Average refers to the average permissible exposure concentration of 8-hour working days and 40-hour working weeks regulated with the time as the weight.

PC-STEL: Permissible Concentration Short Term Exposure Limit refers to the concentration allowed to be exposed for a short time (15 min) under the premise of complying with PC-TWA.

IARC: International Agency for Research on Cancer.

ACGIH: American Conference of Government Industrial Hygienists

STEL: Short Term Exposure Limi.t

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Heath Concentrations.

OSF: Odor Safety Factor.

NOAEL: No Observed Adverse Effect Level. LOAEL: Lowest Observed Adverse Effect Level.

TLV: Threshold Limit Value LOD: Limit of Detection. OTV: Odour Threshold Value.